


IPB Single phase dry type cast resin safety transformers with IP54 protection for outdoor installation.




### Technical characteristics

Rating	200 VA
Input voltage	230/400/460 V
Output voltage	12/24 V
Frequency	50/60 Hz
Protection degree	IP-54
Ambient temperature	45 ºC
Cooling	AN
Temperature rise	Class B - 130ºC
Insulation	Class H - 180ºC
Windings	Class HC - 200 ºC
Test voltage	4,6 kV (1 min, 50 Hz) pri-sec - 3,2 kV (1 min, 50 Hz) pri-earth - 2,5 kV (1 min, 50 Hz) secearth
Standards	IEC/EN/UNE-EN 61558, CE
Mounting	Screws
Weight	7,3 kg

# Electric scheme



# **Dimensions**



Dimensions (AxBxCxDxE): 150x165x190x145x125 mm 7Ø

# **Electrical connection**



≥ 200 VA

Input: 230 V

400 V

460 V

Output: Connection: 1-4 IPB 12 V Bridges: 1-2 / 3-4;

IPD 115 V

Bridges: 6-7 / 8-9

Connection: 6-9

Connection: 1-5

Bridges: 2-3 IPB 24 V

Connection: 6-9 IPD 230 V Bridges: 7-8

Bridges: 2-3

Connection: 1-4



IPB Single phase dry type cast resin safety transformers with IP54 protection for outdoor installation.

#### **Features**

Dry type resin cast transformer

Specially designed for applications in places with risk of direct contact with water or other liquids Advantages of resin technology:

- Protection against corrosive environments
- Protection against high vibration levels
- Protection against electrodynamic efforts
- Reduction of noise level
- Increase of product's lifespan

#### Safety class I

Full power capacity in every conection

Includes lifting eyebolts. Also includes thermal protection against over emperature until 8 kVA -> confirm Possibility of tailor-made manufacturing

# **Applications**

- The IP transformers are specially designed to adapt voltages in control and safety applications and control for voltages for human security in outdoors
- Another important application is the galvanic isolation of facilities for safety reasons, as well as the generation of neutrals referenced to earth

### Available accessories

• Fuse in primary input.

### **Downloads**